

LED PAR20

The PAR20 is a highly efficient LED lamp that uses only eight watts of energy to replace up to a 40-watt halogen PAR20, significantly reducing your carbon footprint while maintaining a very high quality of light. The SKR2008 features industry leading light output, making it ideal for accent, architectural and wall wash lighting in track, recessed and decorative lighting fixtures in retail, high-end residential and office environments. The LED Lamps produce a strong center beam candle power that provides bright and crisp lighting to showcase artwork and products.

PROJECT NAME
CATALOG NUMBER
NOTES
FIXTURE TYPE

FEATURES:

- 120V / 60Hz
- 25,000 hour life at L70 standards
- CRI: >80
- Solid aluminum housing for thermal heat protection
- High output COB chip
- Five year limited warranty
- Dimmable down to five percent
- Suitable for damp locations
- Operating temperature range: - 4° to 113° F



CONSTRUCTION:

LEDs: The SKR2008 features a COB LED package that offers high uniformity and intensity of light with superior thermal performance.

Housing: The body of each lamp is solid die cast aluminum and engineered to efficiently remove heat from the LED package. The white finish is designed to seamlessly integrate the lamp into ceiling cavities.

Base: The PAR20 has a standard E26 base.

Lamp Ordering Information:

Watts	Order Number	Model Number	Incandescent Equivalent	Lumens	CBCP	Beam	Lamp Life (Hrs.)	Dimensions (W"xH")	CCT
8	71758	SKR2008DLED30-136*	35	380	1300	25°	25,000	2.5" x 3.4"	3000
8	71759	SKR2008DLED50-136	35	410	1400	25°	25,000	2.5" x 3.4"	5000

*ENERGYSTAR® rated.

Lighting layouts and spacing criteria available upon request



Max13024

Edificio Pabellón Tec
Ave. Eugenio Garza Sada 427 Ofcna. 38-26
Col. Alta Vista, Monterrey, N.L., CP. 68849

LED PAR20

COMPATIBLE DIMMERS:

Manufacturer	Model#
Lutron	D-600 PH-DK
Lutron	TG-603PGH
Lutron	CTCL-153PDH
Lutron	S-600PR
Leviton	C20-6681-IW

DIMENSIONS:

